


Illuminazione per strade da altezze di montaggio molto basse p.es. ponti

 RAL 9005



 ewo colours




RAZER with schermo



A-Series
1 LED-unit




[Configurator](#)

  
IP66 RoHS IK10




Precision lens optics



AV01
Asymmetric Extra Forward Grazing

Monochrome

 3,000 K
CRI ≥ 70

CRI ≥ 80
on request

Housing

Housing material	Aluminum die-cast
Housing finish	Polyester powder coating* (ewoECP upon request**)
Finish standard colour	ewo colours* (shutter RAL 9005)
Glass	Polycarbonate cover
Mounting options	wall
Fixing	Stainless steel L-bracket

* other colours on request
** ewo three steps process (high quality alloy, pre-treatment, primer) to ensure extreme corrosion resistance

Measurements

Model	I_p ①	$-I_p$ ②	Weight [kg] ③
RAZER + shielding	0.015*	0.019*	1.0

① Projected windage area [m²]
② Lateral windage area [m²]
③ Weight with L-bracket
* Tilt 0°

Performance

Distribution	AG01
Beam angle	-
MacAdam ellipses (SDCM)	≤ 3 SDCM
Nr. of LEDs	8
Luminous flux [lm] (3,000 K)	1,400

Electrical


A-Series

Protection class	II/ III
UNominal [Vdc]	25.6
Ucc max. [Vdc]	300
Current max. [mA]	1,000
LED power [W]	25.6

Operating conditions

Lifetime Visit the [configurator](#) for specific lifetime options

Driver (external) Monochrome

Control Options	
Programming	Stand-alone Constant Lumen Output (CLO)
Control accessories	Further accessories on request